



SAFETY DATA SHEET

1. Identification

Product identifier Propane – Stenched

Other means of identification None.

Recommended use Industrial/Commercial

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information Manufacturer

Company name Global Gas, Inc.
Address 383 Inverness Pkwy
Suite 100
Englewood, CO 80112

Emergency Telephone Number 303-790-2661
24 Hours For any information regarding this SDS or for any additional information on the product, please call 303-790-2661.

2. Hazard(s) identification

Physical hazards	Flammable gases	Category 1
	Gases under pressure	Liquefied gas
Health hazards	Acute toxicity, inhalation	Category 4
	Germ cell mutagenicity	Category 1B
	Carcinogenicity	Category 1A
	Reproductive toxicity	Category 1A
	Specific target organ toxicity, repeated	Category 2 exposure
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Danger
Hazard statement	Extremely flammable gas. Harmful if inhaled. May cause genetic defects. May cause cancer. May damage fertility or the unborn child. May cause damage to Blood through prolonged or repeated exposure. May cause cryogenic burns or injury.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Wear cold insulating gloves/face shield/eye protection. Do not breathe gas. Avoid breathing vapors. Use only outdoors or in a well ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If inhaled: Remove person to fresh air and keep comfortable for breathing. Get immediate medical advice/attention. Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate all ignition sources if safe to do so. In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
Storage	Store in a well-ventilated place. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise	Contact with liquefied gas can cause damage (frostbite) due to classified (HNOC) evaporative cooling.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Propane – Propylene	68606-26-8	90 – 100
Butanes	68513-65-5	0 - 2.5
Ethyl Mercaptan	75-08-1	0 - .01
Other components below reportable levels		3.75

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation	Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory tract irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation. If breathing is difficult, give oxygen. Get medical attention.
Skin contact	GAS: Not applicable. No adverse effects due to skin contact. LIQUEFIED GAS: If frostbite occurs, immerse involved area in warm water (between 100°F/38°C and 110°F/43°C, not exceeding 112°F/44°C). Keep immersed for 20 to 40 minutes. Seek medical assistance.
Eye contact	GAS: No specific first aid measures noted. LIQUEFIED GAS: If frostbite occurs, immediately flush eyes with plenty of warm water (not exceeding 105°F/41°C) for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention immediately.
Ingestion	GAS: Not likely, due to the form of the product. LIQUEFIED GAS: Contact with liquid form may cause frostbite. Get medical attention immediately.
Most important symptoms/effects, acute and delayed	Frostbite, burns. Due to oxygen deficiency inhalation of gas may cause dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation and result in unconsciousness.
Indication of immediate medical attention and special treatment needed	In case of shortness of breath, give oxygen. Provide general supportive measures and treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Powder. Water spray. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from chemical	During fire, gases hazardous to health may be formed. the
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting /instructions	In case of fire and/or explosion do not breathe fumes. DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED. ALWAYS stay away from tanks engulfed in flame. Move containers from fire area if you can do so without risk. Do not direct water at source of leak or safety devices as icing may occur. Use water spray to cool unopened containers. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Cool containers exposed to flames with water until well after the fire is out.
General fire hazards	Extremely flammable gas.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Avoid inhalation of vapors and spray mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. If possible, turn leaking containers so that gas escapes rather than liquid. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Dike far ahead of spill for later disposal. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

Environmental precautions water courses or onto the ground.

Prevent further leakage or spillage if safe to do so. Avoid discharge into drains,

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. All equipment used when handling the product must be grounded. Valve protection caps must remain in place unless container is secured. Close valve after each use and when container is empty. Do not drop, drag, slide or roll cylinders on their sides. Do not subject cylinders to rough handling or to abnormal mechanical shock. Use a suitable hand truck or forklift to move heavier cylinders. Never insert an object (e.g. wrench, screwdriver, pry bar) into cap openings. Use an adjustable strap wrench to remove over-tight or rusted caps. Open valve slowly. Do not heat container by any means to increase the discharge rate of product from the container. Do not breathe vapors or spray mist. Do not breathe gas. Avoid contact with eyes. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. Use care in handling/storage.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Secure cylinders in an upright position at all times, close all valves when not in use. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Ethyl Mercaptan (CAS 75-08-1)	Ceiling	25 mg/m ³ 10 ppm

US. ACGIH Threshold Limit Values Components Type Value

Ethyl Mercaptan (CAS 75-08-1)	TWA	0.5 ppm
-------------------------------	-----	---------

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Ethyl Mercaptan (CAS 75-08-1)	Ceiling	1.3 mg/m ³ 0.5 ppm

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear approved chemical safety goggles.

Skin protection
Hand protection Wear appropriate chemical resistant gloves.
Other Wear appropriate clothing to prevent skin contamination or freezing. Use of an impervious apron is recommended.

Respiratory protection Wear positive pressure self-contained breathing apparatus (SCBA).
Thermal hazards Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Gas.
Form Liquefied gas.
Color Not available.

Odor	Natural gas.
Odor threshold	5000 - 20000 ppm
pH	Not available.
Melting point/freezing point	-309.46 °F (-189.7 °C)
Initial boiling point and boiling range	-44 °F (-42.22 °C)
Flash point	-156.0 °F (-104.4 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Flammable gas.

Upper/lower flammability or explosive limits

Flammability limit – lower (%)	2.2 %
Flammability limit - upper (%)	9.5 %
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	0.58
Solubility (ies)	
Solubility (water)	Negligible
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	842 °F (450 °C)
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	Percent volatile
	100 %

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition	No hazardous decomposition products are known. Products

11. Toxicological information

Information on likely routes of exposure

Inhalation	Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation.
-------------------	--

Skin contact	Contact with liquefied gas may cause frostbite.
Eye contact	Contact with liquefied gas may cause frostbite.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Frostbite, burns. Due to oxygen deficiency inhalation of gas may cause dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness.
Information on toxicological effects	
Acute toxicity	Harmful if inhaled.
Skin corrosion/irritation	Contact with liquefied gas may cause frostbite. Serious
eye damage/eye irritation	Contact with liquefied gas may cause frostbite.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	May cause genetic defects.
Carcinogenicity	May cause cancer.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	
	Not listed.
Reproductive toxicity	May damage fertility or the unborn child.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not likely, due to the form of the product.
Chronic effects	May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulators.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information**DOT**

UN number	UN1075
UN proper shipping name	Liquefied petroleum gas
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	T50
Packaging exceptions	306
Packaging non bulk	304
Packaging bulk	314, 315

IATA

UN number	UN1075
UN proper shipping name	Liquefied petroleum gas
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	No.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number	UN1075
UN proper shipping name	LIQUEFIED PETROLEUM GAS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Ethyl Mercaptan (CAS 75-08-1) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories**

Immediate Hazard – Yes
 Delayed Hazard - Yes
 Fire Hazard – Yes
 Pressure Hazard – Yes
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes **chemical****SARA 313 (TRI reporting)**

Not regulated.

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Ethyl Mercaptan (CAS 75-08-1)

Safe Drinking Water Act Not regulated.**(SDWA)****US state regulations****US. Massachusetts RTK - Substance List**

Ethyl Mercaptan (CAS 75-08-1)

US. New Jersey Worker and Community Right-to-Know Act

Ethyl Mercaptan (CAS 75-08-1)

US. Pennsylvania Worker and Community Right-to-Know Law

Ethyl Mercaptan (CAS 75-08-1)

US. Rhode Island RTK

Ethyl Mercaptan (CAS 75-08-1)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region (yes/no)*	Inventory name	On inventory
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16.1 Other information, including date of preparation or last revision

Issue date	June 1, 2015
Revision date	-
Version #	01
HMIS® ratings	Health: 2* Flammability: 4 Physical hazard: 3

NFPA ratings



16.2 Disclaimer **Disclaimer of Expressed and implied Warranties:**

The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THE INFORMATION PROVIDED ABOVE THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above and the product are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purposes and on the condition that they assume the risk of their use. In addition, no authorization is given nor implied to practice any patented invention without a license.

Global Gas, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

16.3 OSHA Refer to OSHA 29 CFR 1910.1200

16.4 Precautionary Statement(s):

P210: Keep away from heat/sparks/open flames/hot surfaces – No smoking.
P243: Take precautionary measures against static discharge.
P381: Eliminate all ignition sources if safe to do so.
P377: Leaking gas fire. Do not extinguish, unless leak can be stopped safely.
P410+P403: Protect from sunlight. Store in a well ventilated place.